

## Prescription Document for IN485MIT001I000

**Product type:** The IN485MIT001I000 is a BACnet MS/TP gateway compatible with Mitsubishi Electric domestic, Mr.Slim, and City Multi lines air conditioning systems.

**Manufacturer:** HMS Industrial Networks SLU.

**Product description:** Connect this gateway directly to an AC indoor unit to control main functions, such as operating mode, fan speed, temperature setpoint..., and to monitor errors, alarms, and some internal variables. The gateway configuration is very easy: just set the DIP switches according to your needs. No configuration software or power supply is required.

**Installation:** DIN rail, wall, or inside the indoor unit (in some AC models only).

### Main features:

- BTL seal ensures full interoperability with BACnet devices.
- Supports BACnet MS/TP.
- Configuration with onboard DIP switches.
- Quick and easy installation: Set the DIP switches, plug, and play.
- External power supply not required.
- Simultaneous control of the AC unit by the IR remote controller and by BACnet MS/TP.
- Reduced dimensions: 93 x 53 x 58 mm.
- Mountable on DIN rail, wall, or even inside the indoor unit in some models of AC.
- Significant reduction of the HVAC system energy consumption.
- Total control and monitoring of the AC unit from the BACnet system, including the AC unit's internal variables, running hours counter (for filter maintenance control), and error indication, among many other functions.
- Three-year warranty.

**Equipment and accessories:** Intesis gateway, installation sheet, and AC connection cable.

### Standards, guidelines, and certificates:

- BACnet certificate.
- CE conformity to EMC directive (2014/30/EC) and low-voltage directive (2014/35/EC).
- EN 61000-6-3, EN 61000-6-2, EN 62368-1.
- Compliant with RoHS 2 directive (2011/65/EU).

### Technical specifications:

<b>Enclosure</b>	Plastic, type PC (UL 94 V-0) Net dimensions (DxWxH): 93 x 53 x 58 mm / 3.7 x 2.1 x 2.3" Color: Light grey. RAL 7035
<b>Weight</b>	85 g (3 oz)
<b>Terminal wiring for low-voltage signals</b>	Per terminal: solid wires or stranded wires (twisted or with ferrule) 1 core: 0.5 to 2.5 mm <sup>2</sup> (24 to 11 AWG) 2 cores: 0.5 to 1.5mm <sup>2</sup> (24 to 15 AWG) 3 cores: not permitted
<b>Mounting</b>	DIN rail, wall, or even inside the indoor unit in some models of AC.
<b>BACnet MS/TP port</b>	1 x EIA-485 pluggable terminal block (3 poles: B, A, and SG) with 120 Ω resistor termination and polarisation configurable by DIP switch
<b>AC unit port</b>	1 x Specific socket
<b>LED indicators</b>	2 x Communication status
<b>DIP switches</b>	SW1: Baudrate configuration SW2: MAC address and temperature unit SW3: Bus polarization and termination
<b>Operational and storage temperature</b>	Celsius: Op: 0 to +70°C; St: -20 to 85°C Fahrenheit: 32 to 158°F; St: -4 to 185°F
<b>Operational and storage humidity</b>	5% to 95%, non-condensing
<b>Isolation Voltage</b>	1500 VDC
<b>Isolation resistance</b>	1000 MΩ